

Creative TerraTex Paint

Cement Based Colour Texture Coating

DESCRIPTION

Creative TerraTex Paint is a cement-based colour textured coating material. It is a decorative coating made from white cement, mineral fillers, various adhative, water proof chemical and pigments. It provides a durable, weather-resistant, and textured finish for interior and exterior walls, offering good adhesion, breathability, and very long-lasting colour and waterproofing guarantee.

SCOPE OF USE

It is suitable for interior and exterior wall surfaces, concrete, plaster, and masonry. Ideal for residential, commercial, and industrial buildings to achieve decorative, durable, and weather-resistant textured finishes.



TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Composition		White portland cement, marble chips, hydrated lime, various cellulose powders, colour pigment, and chemical improving agents
Appearance		Colours powder
Mixing Ratio		5/6 kg of water for 25 kg bag
Compressive Strength		6N/mm ² @ 28 bags
Flexural Strength		1 N/mm ² @ 28 days
Working time		Approx 45/50 minutes
Specification		BS EN 998-1 BS EN 13914-2



KEY ADVANTAGES

- Durable and weather-resistant.
- Provides attractive textured/Terratex finish.
- Good adhesion on concrete, plaster, and masonry.
- Breathable, preventing moisture buildup.
- UV and fungal resistant.
- Long-lasting colour retention.

SURFACE PREPARATION

Surface must be cementitious and clean from dust, oil loose particles. Repair cracks and uneven areas with any dampness before application.



MIXING

Pre-mix texture paint powder with clean water as per requirements, depends on the surface condition & environment. Use slow-speed drill mixer for uniform consistency and creamy paste

APPLICATION

The surface should be wetted prior to material application. But water will not accumulate anywhere. The water-mix creamy past apply prepair cementitious surface. 1st coat with plastic trowel/roller to desired thickness (2-3mm) create texture by roller, trowel or pattern tools.

CURING

Cement-based colour texture paint curing is usually not required. Better, Water spray may be done once/twice after 12/24 hours, if applied in hot, dry, or windy weather, to prevent surface shrinkage.

GENERAL INFORMATION

Shelf Life 12 months from date of manufacture when stored under warehouse conditions in original unopened packing.
Extreme temperature / humidity may reduce shelf life.

Cleaning Clean all equipment and tools with water immediately after use.

HEALTH AND SAFETY

PPE's	Gloves, goggles and suitable mask must be worn.
Precautions	Contact with skin, eyes etc. must be avoided. If swallowed seek medical attention immediately.
Hazard	Regarded as non-hazardous for transportation.
Disposal	Do not reuse containers. To be disposed of as per local rules and regulations.
Additional Information	Refer MSDS. (Available on request)

