

Creative Wall Flexi Paint

All-Weather Protection Flexible Wall Paint

DESCRIPTION

Creative Wall Flexi Paint is flexible, all-weather protective water-based acrylic paint designed to provide long-lasting durability and excellent resistance moisture UV rays, and harsh climate breathable coating suitable for both interior and exterior surfaces.

MAIN INGREDIENT

Acrylic polymer emulsion pigment, (From color & opacity) Fillers & extenders, water, additives, wetting, leveling, antifoaming preservation.



SCOPE OF USE

It is suitable for exterior and interior walls, concrete, plastered surfaces and masonry structures. Ideal for protecting buildings, facades and other exposed surfaces from weathering, moisture and UV degradation

TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Appearance		Smooth matt or Sheen finish.
Base		Water-base acrylic.
Colour		With and custom shades
Coverage		8-10 m²/L/coat.
Drying time		Touch dry 30-45 min. Recoat 4-6 hrs.
Application Tools		Brush, roller or Spray
Recommended Coat		2 coats
Self life		12 months in sealed container

KEY ADVANTAGES

- Excellent weather and UV resistance
- Flexible and crack-bridging film.
- Water - Repellent yet breathable coating
- Strong adhesion to various substrates
- Long - Lasting color & finish durability.

SURFACE PREPARATION

Ensure the surface is clean dry and free from dust, oil, grease, loose barflies and old paint. Repair cracks and defects before application for best results.



APPLICATION METHOD

Stir paint well before use, apply by brush, roller, or spray in 2 coats with adequate drying time between coats ensure uniform coverage on a properly prepared surface.

COVERAGE

Approximately 8-10 m²/ litter / coat, depending on surface texture, porosity and application method.

SPECIAL NOTE

- Do not apply on damp or wet surface
- Protect from grain and direct sunlight during drying
- Stir well before use.
- Store a cool, dry place away from direct heat and sunlight

PACK SIZE

10 kg Bucket

GENERAL INFORMATION

Shelf Life	12 months from date of manufacture when stored under warehouse conditions in original unopened packing.
	Extreme temperature/humidity may reduce shelf life.
Cleaning	Clean all equipment and tools with water immediately after use.

HEALTH AND SAFETY

PPE's	Gloves, goggles and suitable mask must be worn.
Precautions	Contact with skin, eyes etc. must be avoided. If swallowed seek medical attention immediately.
Hazard	Regarded as non-hazardous for transportation.
Disposal	Do not reuse containers. To be disposed off as per local rules and regulations.
Additional Information	Refer MSDS. (Available on request)

