

# Creative Wall Putty

Waterproof, High-quality, multipurpose white putty powder

## DESCRIPTION

**Creative Wall Putty** is a pre-mixed, ready-to-use fine white powder for leveling interior and exterior walls. It provides a smooth durable, and water-repellent finishes with excellent crack resistance. The composition is high-quality white cement, titanium, polymers, cellulose fiber, fillers and hydrophobic additives ensure superior adhesion, easy application and long lasting performance ideal as a base for all types of paint finishes.



## SCOPE OF USE

Suitable for interior and exterior walls, new or old masonry, plaster, concrete, bricks, and blocks. Provides a smooth, durable, crack-and water-resistant surface for painting in both new construction and repair works.

## SURFACE PREPARATION

Ensure the surface is cementitious, clean, sound, and free from dust, grease, loose particles, or paint. Repair any cracks or holes, and lightly dampen the surface before applying the wall putty.

## TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Appearance		Fine white powder
Layer thickness		0.5-3 mm
Drying time		12-24 hrs before painting
Water Requirement		30-35% by weight
Compressive Strength		≥ 5 MPa.

## KEY ADVANTAGES

- Smooth & easy to apply.
- Crack-resistant & flexible.
- Strong adhesion to masonry & plaster.
- Paintable & durable.



## MIXING & APPLICATION

Add putty powder gradually to clean water and mix to a smooth, lump-free paste. Apply 0.5-3 mm thick coat using a trowel or putty knife. Allow to dry 12-24 hours before sanding or painting. For best results, apply 2 coats if needed. Putty has to be protected from direct exposure to sunlight, wind, and rain during the application.

## GENERAL INFORMATION

Shelf Life	12 months from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature / humidity may reduce shelf life.
Cleaning	Clean all equipment and tools with water immediately after use.

## HEALTH AND SAFETY

PPE's	Gloves, goggles and suitable mask must be worn.
Precautions	Contact with skin, eyes etc. must be avoided. If swallowed seek medical attention immediately.
Hazard	Regarded as non-hazardous for transportation.
Disposal	Do not reuse containers. To be disposed of as per local rules and regulations.
Additional Information	Refer MSDS. (Available on request)



**Creative Chemical Vietnam Co. Ltd.**

No-15, Street-10A, Bien Hoa Industrial Zone 1, Bien Hoa City, Dong Nai, Vietnam  
Phone: (+84) 251 8877 400, (+84) 61 3836 125, Email: [info@creativechemical.net](mailto:info@creativechemical.net), Web: [creativechemical.net](http://creativechemical.net)

Creative Chemical products are produced with ISO 9001:2015 standard terms and conditions. So it's customer responsibility to maintain and follow up the TDS and weather forecast carefully. We can not guarantee the application and end use as it depends on various conditions and weather.